

The New-Breed Booster with a Bonus

The unique FB-2 Feedbacker/Booster packs a world of expressive, versatile boost into a single stompbox. Seamlessly morph from flat, clean boost that doesn't spoil the nuance of the original tone to an amazing mid boost for high-gain solos, or dial up a bright and clear treble boost to lighten the tone. And that's only half of the picture...the FB-2 can generate smooth and natural amp feedback as well. The FB-2's versatile tone, simple operation, and low noise are made possible through BOSS' latest technology and decades of know-how.



- ▶ Wide tonal variety, from flat, clean boost to powerful mid-boost and bright, clear treble boost
- ▶ Boost characteristics can be changed continuously and smoothly from one knob
- ▶ Responds expressively and accurately to picking nuances, even at high-boost settings
- ▶ Versatile tone, simple operation, and low noise
- ▶ Advanced Feedback function provides smooth and natural amp feedback

FB-2 Specifications

■ Nominal Input Level -20 dBu **■ Input Impedance** 1 M Ω **■ Nominal Output Level** -20 dBu **■ Output Impedance** 1 k Ω **■ Recommended Load Impedance** 10 k Ω or greater
■ Power Supply DC 9 V: Carbon-zinc battery (9 V, 6F22) / Alkaline battery (9 V, 6LR61), AC Adaptor (PSA series: sold separately) **■ Current Draw** 45 mA (DC 9 V) * Expected battery life under continuous use: Carbon: 2.5 hours, Alkaline: 9 hours. These figures will vary depending on the actual conditions of use. **■ Dimensions** 73 (W) x 129 (D) x 59 (H) mm; 2-7/8 (W) x 5-1/8 (D) x 2-3/8 (H) inches **■ Weight** 0.44 kg; 1 lb (including battery) **■ Accessories** Owner's Manual, Leaflet ("USING THE UNIT SAFELY," "IMPORTANT NOTES," and "Information"), Alkaline battery (9 V, 6LR61) **■ Option (sold separately)** AC Adaptor (PSA series)

* 0 dBu = 0.775 Vrms

* The specifications are subject to change without notice.